

Gen-Eye® Comparison Chart

	Gen-Eye POD®	Gen-Eye Prism®	Gen-Eye SDN®	Gen-Eye SDW®	Gen-Eye SDP®	Gen-Eye Micro-Scope®
Line Capacity						
Standard Reel	3" to 10"	3" to 10"	3" to 10"	3" to 10"	3" to 10"	
Mini-Reel	2" to 4"	2" to 4"	2" to 4"	2" to 4"	2" to 4"	
Micro-Reel						1-1/2" to 3"
Reel Capacity						
Standard Reel	200'	200', 300' or 400'	200', 300' or 400'	200', 300' or 400'	200', 300' or 400'	
Mini-Reel	125' or 175'	100' or 200'	100' or 200'	100' or 200'	100' or 200'	
Micro-Reel						33' or 100'
Probe-Rod						3'
Rod Size						
Standard Reel	.475" Gel-Rod®	.475" Gel-Rod	.475" Gel-Rod	.475" Gel-Rod	.475" Gel-Rod	
Mini-Reel	.400" Gel-Rod	.400" Gel-Rod	.400" Gel-Rod	.400" Gel-Rod	.400" Gel-Rod	
Micro-Reel						.200" Push-Rod
Probe-Rod						.400 Probe-Rod
Camera Dimensions						
Standard	1.625" x 2.7" L	1.625" x 2.7" L	1.625" x 2.7" L	1.625" x 2.7" L	1.625" x 2.7" L	
Mini	1.125" x 1.74" L	1.125" x 1.74" L	1.125" x 1.74" L	1.125" x 1.74" L	1.125" x 1.74" L	
Micro						1" x 1.38" L
Probe						.425" x 1.15" L
Sensitivity						
Standard	0.5 Lux	0.5 Lux	0.5 Lux	0.5 Lux	0.5 Lux	
Mini	0.008 Lux	0.008 Lux	0.008 Lux	0.008 Lux	0.008 Lux	
Micro						0.5 Lux
Probe						0.5 Lux
Lighting						
Standard	16 White LEDs 88K MCD	16 White LEDs 88K MCD	16 White LEDs 88K MCD	16 White LEDs 88K MCD	16 White LEDs 88K MCD	
Mini-Reel	4 Super Bright LEDs 78K MCD	4 Super Bright LEDs 78K MCD	4 Super Bright LEDs 78K MCD	4 Super Bright LEDs 78K MCD	4 Super Bright LEDs 78K MCD	
Micro						12 White LEDs
Probe						6 White LEDs
White Balance	Auto High Speed	Auto High Speed	Auto High Speed	Auto High Speed	Auto High Speed	Auto High Speed
Standard Reel Dimensions"	29"L x 16"W x 33.5"H	29"L x 16"W x 33.5"H	29"L x 16"W x 33.5"H	29"L x 16"W x 33.5"H	29"L x 16"W x 33.5"H	17"L x 16-1/2"W 7-1/2"H
Mini Reel Dimensions	18"L x 16"W x 19"H	18"L x 16"W x 19"H	18"L x 16"W x 19"H	18"L x 16"W x 19"H	18"L x 16"W x 19"H	N/A
LCD Monitor Size	7"	10.4"	10.4"	10.4" Sunlight Readable	N/A	3.5"
Command Module						
Dimensions	9.5" L 7" H 3" D	9.5" H 5.5"W 3" D	10.5"L x 14"W 6"H (Closed) 12.5"H (Open)	10.5"L x 14"W 6"H (Closed) 12.5"H (Open)	10.5"L x 14"W 6"H (Closed) 12.5"H (Open)	10-1/4" L 15-1/4" W 1-7/8" H
Weight	N/A	3 lbs (1.4 Kg)	12 lbs (5.5 Kg)	12 lbs (5.5 Kg)	14 lbs (6.4 Kg)	1.5 lbs (.7 Kg)
Wi-Fi	No	Yes	No	Yes	Yes	No
Audio	No	No	Yes	Yes	Yes	Yes
Video Format	NTSC or PAL	NTSC or PAL	NTSC or PAL	NTSC or PAL	NTSC or PAL	NTSC or PAL
Recording Device	External Connection	Wi-Fi	SD Card	SD Card or Wi-Fi	SD Card or Wi-Fi	SD Card
Power Source	110v/60Hz AC 15v DC	110v/60Hz AC 12v DC	110v/60Hz AC 12v DC	110v/60Hz AC 12v DC	110v/60Hz AC 12v DC	110v/60Hz AC 5v DC
Battery				4 hr. Rechargeable		4 hr. Rechargeable
Operating Temp.	14°F to 122° F (-10°C to 50°C)	14°F to 122° F (-10°C to 50°C)	14°F to 122° F (-10°C to 50°C)	14°F to 122° F (-10°C to 50°C)	14°F to 122° F (-10°C to 50°C)	14°F to 122° F (-10°C to 50°C)

General General Wire Spring Co.
PIPE CLEANERS
McKees Rocks, PA 15136 USA
800-245-6200 or 412-771-6300

www.drainbrain.com

The toughest tools down the line.™



MADE IN USA

C-GECOMP-0816