

Speedrooter XL[®]

Long Distance Power – Easy Drum Changes



With easily interchangeable drums, the Speedrooter XL gives you long distance clog-busting power in 3" to 10" lines – up to 200 feet. The rugged, easy-to-manuever Speedrooter XL sports a powerful 3/4 hp motor to drive the cable down longer runs and clear tough stoppages.

Change drums to add cable lengths or swap cable sizes with ease. Just loosen three knobs and remove the drum. Switch between 3/4" or 5/8" Flexicore cables in the large drum - General's see through inner cage lets you quickly gauge how much cable remains - or substitute the small drum with 100 feet of 1/2" Flexicore cable for smaller lines.

The variable speed Power Cable Feed offers raw driving and pulling power for long, tough jobs – feeding and retrieving 3/4", 5/8" and 1/2" cables. To adjust to each cable size, simply turn a knob on top of the feed – no screwdriver required!

One person can easily load the Speedrooter XL onto a truck. The machine's frame slides smoothly from the loading wheel to the handle to the stair climbers and finally to the wheels. The adjustable height, sweep-back handles also provide maximum maneuvering leverage. And the durable design features a braced frame at key stress points, front and rear drum supports for longer bearing wear, and Flexicore[®] cable.



One person easily loads the Speedrooter XL onto a truck. The swept-back handles and loading wheel give you the needed leverage.

General *General Wire Spring Co.*
PIPE CLEANERS McKees Rocks, PA 15136 USA
800-245-6200 or 412-771-6300
www.drainbrain.com



The toughest tools down the line.™

Speedrooter XL® Units

Complete and ready to operate

| | |
|--------|---|
| PSXL-A | With 100 ft. x 3/4" (100EM5) cable in large drum, 100 ft. x 1/2" (100EM3) cable in small drum, and COCS combination cutter set. |
| PSXL-C | 100 ft. x 3/4" (100EM5) cable and SRCS cutter set. |
| PSXL-D | With 100 ft. x 3/4" (100EM5) cable, an additional Large Drum (SXL-450) with 100 ft. x 3/4" (100EM5) cable, and SRCS Cutter Set. |
| PSXL-E | With 100 ft. x 5/8" (100EM4) cable and SRCS cutter. |
| PSXL-F | with 100 ft. x 5/8" (100EM4) cable, an additional Large Drum (SXL-450) with 100 ft. x 5/8" (100EM4) cable, and SRCS Cutter Set. |

Bold listing denotes the best selling model.

Flexicore® Wire Rope Center Cables

Heavy gauge wire is coiled around 49 strand wire rope and then heat treated. This cable has unequalled strength and the right amount of flexibility. It's so tough it has a one year warranty against defect or breakage.



Guide tube

Guide tube reduces cable whipping and keeps your hands off the spinning cable. Tube is 30" long. Five foot extensions are available.



V-belt stair climbers

V-belt stair climbers let you take the Speedrooter XL up a flight of stairs yourself.



Small Drum

Holds up to 100 ft. of 1/2" Flexicore cable.

Specifications:

- Weight:** 115 lbs. (52 kg) without cable.
- Dimensions:** 26" deep, 22" wide, 41" high (66 cm x 56 cm 104 cm).
- Large Drum:** Equipped with inner drum cage and distributor tube. Holds 100 ft x 3/4" or 5/8" cable.
- Small Drum:** Equipped with inner drum and distributor tube. Holds 100 ft. x 1/2" cable.
- Drum Removal:** Loosen three knobs and lift drum off frame. A smaller V-belt is required for the small drum and is standard with the PSXL-A.
- Motor:** 3/4 hp with capacitor, forward-off-reverse switch, 20 ft. power cord and ground fault circuit interrupter.
- Foot Switch:** Pneumatic, with no electrical contact between pedal and motor.
- Power Cable Feed:** Drives and retracts at variable speed of up to 20 ft. per minute.

- Wheels:** 10" Heavy-duty wheels with roller bearings.
- Stair Climbers:** Heavy-duty V-belts running on nylon rollers.
- Wheel Brake:** Keeps machine in place on the job or in the truck.
- Truck Loading Wheel:** Enables one person to lift machine onto bed of truck.
- Tool Box:** Attached to rear of machine. Holds all cutters except Flexible leader.
- Leather Gloves:** With double-reinforced palm for hand protection when guiding cable.
- Cables:** Left wound Flexicore® wire rope center 3/4" diameter for 4" to 10" lines and 3" lines without sharp bends; 5/8" diameter for 3" to 6" lines; 1/2" diameter for 2" to 3" lines.
- Cutters:** Cutter Sets for 3/4" 5/8" and 1/2" cables (see below).

Senior Cutter Set – Catalog #SRCS

| Cutter | Part Number | Application |
|------------------------------|--------------|--|
| Spear Head | SHD | Starting Drill (Gets Water Flowing) |
| 3" and 4" Side Cutter Blades | 3SCB 4SCB | For cutting and scraping |
| 2" U-Cutter | 2UC | For cutting and scraping |
| 3" Heavy Duty Saw Blade | 3HDB | For roots and other stoppages |
| 4" Rotary Saw Blades | 4RSB | For roots and other stoppages |
| Large Retrieving Tool | RTR-2 | For removing loose objects and broken cable |
| 26" Flexible Leader | LE-3 | Helps cable get around tight bends and traps |

Combination Cutter Set – Catalog #COCS

(Includes Senior Cutter Set plus cutters listed below)

| Cutter | Part Number | Application |
|-----------------------|-------------|--|
| Arrow Head | AH | Starting Drill (Gets Water Flowing) |
| 1-1/2" U-Cutter | 1-1/2 UC | For cutting and scraping |
| 2" Side Cutter Blades | 2SCB | For cutting and scraping |
| Small Retrieving Tool | RTR-1 | For removing loose objects and broken cable |
| 13" Flexible Leader | LE-1 | Helps cable get around tight bends and traps |