Spectrooter 92R[®] Automatic Feed Easier handling – same toughness.

The Speedrooter 92R has root cutting power combined with a power cable feed to take a lot of the work out of clearing stoppages.

The feed drives 3/4" and 5/8" cables and has the pulling power to get the cable out of the line even on long, tough jobs. To adjust for 3/4" or 5/8" cables, you simply turn the knob on top of the feed. The cable runs though a guide spring attached to the feed into the drain opening, making it a hands-off operation.

Getting to and from the job is easier, because the Speedrooter has ten-inch wheels, V-belt stair climbers, and a loading wheel mounted on the handle to help you lift the machine into a truck. A capacitor start 1/3 hp motor drives the machine. Standard safety features include air foot pedal, ground fault circuit interrupter and safety slip clutch.



Folding Handle Handle folds to take less space in car trunk.



Portability, Convenience and Safety Equipped with ten inch wheels, stair climbers, tool box, and ground fault circuit interrupter.

Power Cable Feed: Drives or retracts cable at variable speed without having to reverse motor rotation.

Leather Gloves: With double-reinforced palm, for hand protection when guiding cable. Cutters:

See Parts and Accessories on page 14.

Cables: 3/4" diameter for 4" to 10" lines and 3" lines without sharp bends; 5/8" diameter for 3" to 6" lines.

Truck Loading Wheel: Enables one person to lift machine into truck bed.

Tool Box: Attached to rear of machine.

Stair Climbers: V-belts running on nylon rollers.

Instructional Video included.







Pneumatic, with no electrical contact between pedal and motor.

McKees Rocks, PA 15136 USA 800-245-6200 or 412-771-6300



© General Wire Spring Co. 2016

Specifications:

115 lbs. without cable. (52 kg).

26" D; 22" W; 41" H (66 cm x 56 cm x 104 cm).

20 ft. power cord and ground fault circuit interrupter.

Equipped with inner drum cage and distributor tube spring; holds 100 ft. x 3/4" or

1/3 hp with capacitor start, overload protection, and Forward/Off/Reverse switch.

10" semi-pneumatic with roller bearings. Passive brake locks machine during

Weight:

Cage:

5/8" cable.

Motor:

Wheels:

operation.

Foot Switch:

Safety Slip Clutch:

Protects cable and operator.

Dimensions:

The toughest tools down the line.™

