

Looking for a cleaner way to clean drains? The Model DRZ-PH is the answer. Light and powerful for a machine of its size, the Model DRZ-PH is ideal for clearing clogged sinks, tubs, and laundry drains in 1-1/4" to 3" drain lines up to 50 feet long.

The variable speed power cable feed gives you complete control as it feeds and retrieves the cable at up to 16 ft. per minute. The four foot guide tube means you never have to touch the cable so your hands, and the jobsite, stay clean.

Operate the machine horizontally on the kitchen counter or vertically on the floor next to the tub. The silent motor won't disturb your customers while on the job. Use the pneumatic pedal to keep your hands free to control the feed and guide hose.

The rust resistant aluminum drum carries up to 50' of 1/4" or 5/16", or 35' of 3/8" Flexicore wire rope center cable. A quick-change cartridge system allows you to switch to a different diameter cable without pulling the old cable out of the drum.

Weighing as little as 30 lbs. this light-weight machine is easy to handle. Use the carrying handle on top to carry to and from the job.

### **Flexicore® Cable**

# Wire Rope Center Construction

### 

Heavy-gauge wire coiled tightly around 49-strand aircraft-type wire rope and heat treated. Has unequalled strength and the right amount of flexibility. So tough it carries a one-year warranty against defect or breakage. Flexicore Patent Nos. 2.244,735 and 2.849.870

# **DRZ-PH Specifications:**

Weight: 30 lbs. (13.6 kg) (without cable).

### **Dimensions:**

20" deep (w/o Guide Hose) x 11" wide x 15" high (51 cm x 28 cm x 38 cm).

# Drum:

Heavy gauge stamped aluminum with inner drum to prevent cable tangling.

# Power Cable Feed:

Variable Speed; Drives 1/4", 5/16" and 3/8" cables.







### **Economy Drain Cleaner**

The Model DRZ less expensive unit uses a Quick-Grip™ chuck instead of the variable speed power cable feed, and the cable is housed in a tough impact resistant plastic drum.

### Capacity:

50 ft. of 1/4" or 5/16" cable; 35 ft. of 3/8" cable. All cables are left hand wound and reinforced with a wire rope center.

# Cutter Set: See page 30.

# Motor:

1/5 hp, with forward-off-reverse switch, fuse protected.

# Foot Pedal:

Pneumatic foot pedal leaves operator's hands free to control cable.