

# Flat Sewer Rod

**A Sturdy Tool for Cleaning Drain Lines and Sewers**

Oil tempered spring steel is resistant to rusting and kinking. The rod is bolted to the frame at the back, so it can't spring out of the frame when you near the end. A comfortable, efficient Quick-Grip Handle makes the work go faster.



All sizes furnished with Quick-Grip Handle and Roller Head.

| Pipe Size                  | Catalog Number | Feet      | Weight Pounds with Holder |
|----------------------------|----------------|-----------|---------------------------|
| 1/2" x 1/16"<br>2" thru 3" | 50 B<br>100 B  | 50<br>100 | 7-1/2<br>12-1/2           |
| 3/4" x 1/16"<br>2" thru 4" | 50 C<br>100 C  | 50<br>100 | 10<br>18                  |
| 1/2" x 1/8"<br>2" thru 4"  | 50 H<br>100 H  | 50<br>100 | 14<br>22                  |
| 3/4" x 1/8"<br>4" thru 6"  | 50 D<br>100 D  | 50<br>100 | 19<br>35                  |

**Flat Sewer Rod Cutter  
Revolving Roller Head**



| Catalog No. | For Rod Size | Diameter Head | Weight Pounds |
|-------------|--------------|---------------|---------------|
| 1-R         | B            | 1-1/8"        | 1/4           |
| 2-R         | C, H, and D  | 1-1/2"        | 1/2           |

# Drain Flusher

**For the Do It Yourself Market**

Just attach to garden hose and slide Drain Flusher into drain. Water expands Flusher to size of pipe. Then water pressure pushes stoppage down the line.

Equipped with back-flow preventer on the inlet side. Made of tough reinforced nylon to resist punctures. Far more durable than rubber. Narrow profile and internal flat spring help work Drain Flusher around bends. Blister packed on three-color cards.



| Number No | Size   | Weight Pounds |
|-----------|--------|---------------|
| 1.5DF     | 1-1/2" | 1/2           |
| 2.5DF     | 2-1/2" | 1/2           |
| 3DF       | 3"     | 3/4           |
| 4DF       | 4"     | 1             |
| 6DF       | 6"     | 1.25          |



# Test Plugs



With rugged cast aluminum body, smoothly turning cast iron wing nut, and live rubber ball. Rugged construction throughout. Available in 1-1/2", 2", 3" and 4" sizes.