

# Comparison Chart

## Power Drain Cleaners

|  | Typical Applications   | For Use In Following Pipe Sizes                            | Maximum Capacity  | Operating Weight                          | Maximum Recommended Distance   | Motor Horsepower             |
|--|--|--|---|---|--|------------------------------|
| <b>Super-Vee</b><br>Page 6                           | Sinks, Bathtubs,<br>Roof Stacks  | 1-1/4" – 3"<br>(30 mm x 75 mm)                             | 35 ft. x 3/8", or<br>50 ft. x 1/4" or 5/16"<br>(10.5 m x 9.5 mm)<br>(15 m x 7.9 mm) | 16 lbs. with<br>5 ft. x 3/8"<br>(7 kg)    | 50 ft.<br>(15 m)   | 3.2 amp<br>Variable Speed    |
| <b>Power-Vee</b><br>Page 7                           |  |  |   | 34 lbs. (15kg)                            |  |                              |
| <b>Drain Rooter PH</b><br>Page 8                     |  |  |   | 30 lbs. (13 kg)                           |  |                              |
| <b>Model DRZ-PH</b><br>Page 9                        |  |  |   |   |  |                              |
| <b>Mini-Rooter Pro</b><br>Page 12                    | Small Drains,<br>Inside Work, On Roofs   | 2" – 3" and most 4"<br>(50 mm – 100 mm)<br>(Not For Roots) | 75 ft. x 3/8"<br>or 50 ft. x 1/2"<br>(22.5 m x 9.5 mm or<br>15 m x 12.7 mm)         | 62 lbs. With<br>75 ft. x 3/8"<br>(28 kg)  | 75 ft.<br>(22.5 m)   | 1/3 hp                       |
| <b>Mini-Rooter XP</b><br>Page 13                     |  |  |   | 92 lbs. With<br>75 ft. x 3/8"<br>(42 kg)  |  |                              |
| <b>Sewerooter T-4</b><br>Page 14                     | Small Drains<br>with 9/16" Cable;<br>Roots with 5/8" Cable                     | 3" – 6"<br>(75 mm – 150 mm)                                | 100 ft. x 9/16"<br>75 ft. x 5/8"<br>(30 m x 14.2 mm)<br>(22.5 m x 15.8 mm)          | 158 lbs.<br>(72 kg)                       | 150 ft.<br>(45 m)  | 1/3 hp                       |
| <b>Speedroooter 92</b><br>Page 15                    | Main Lines, Roots,<br>Difficult Obstructions                                   | 3" – 10"<br>(75 mm – 250 mm)                               | 100 ft. x 5/8" or 3/4"<br>(30 m x 15.8 mm<br>or 19 mm)                              | 220 lbs.<br>(100 kg)                      | 200 ft.<br>(60 m)  | 1/2 hp<br>(Optional 3/4 hp)  |
| <b>Speedroooter XL</b><br>Page 16                    | Main Lines, Roots with<br>5/8" or 3/4" Cable; Small<br>Drains with 9/16" Cable | 3" – 10"<br>(75 mm – 250 mm)                               | 100 ft. x 9/16,<br>5/8" or 3/4"<br>(30 m x 14.2 mm,<br>15.8 mm or 19 mm)            | 220 lbs.<br>(100 kg)                      | 200 ft.<br>(60 m)  | 3/4 hp                       |
| <b>Maxi-Rooter</b><br>Page 17                        | Main Lines, Roots,<br>Difficult Obstructions                                   | 3" – 10"<br>(75 mm – 250 mm)                               | 125 ft. x 3/4"<br>150 ft. x 5/8"<br>(37.5 m x 19 mm)<br>(45 m x 15.8 mm)            | 250 lbs.<br>(114 kg)                      | 200 ft.<br>(60 m)  | 3/4 hp                       |
| <b>Root 66</b><br>Page 18                            | Small Drains, Inside<br>Work, On Roofs   | 1-1/4" – 4"<br>(30 mm – 100 mm)                            | Not Applicable  | 42 lbs.<br>Without<br>Sections<br>(19 kg) | 125 ft. x 5/8" Sectional<br>150 ft. x 7/8" Sectional<br>(38 m x 15.8 mm)<br>(45 m x 22.4 mm) | 1/2 hp                       |
| <b>Rodrunner</b><br>Page 19                          | Main Lines, Roots,<br>Difficult Obstructions                                   | 3" – 10"<br>(75 mm – 250 mm)                               | Not Applicable  | 90 lbs. Without<br>Sections<br>(41 kg)    | 300 ft.<br>(90 m)  | 3/4 hp                       |
| <b>Rodrunner Model E</b><br>Page 19                  | Main Lines, Roots,<br>Difficult Obstructions                                   | 3" – 10"<br>(75 mm – 250 mm)                               | Not Applicable  | 185<br>Without<br>Sections<br>(84 kg)     | 500 ft.<br>(150 m)   | 6.5 hp gas Engine            |
| <b>Flexi-Rooter 100</b><br>Page 24-25                | Grease, Debris, Roots,<br>Descaling, Wall to Wall<br>Drain Cleaning            | 2" – 4"<br>(50 mm – 100 mm)                                | 50 ft.<br>(15 m)  | 68 lbs.<br>With 50 ft. Shaft<br>(31 kg)   | 75 ft.<br>(22.5 m)   | 4 amp<br>Variable Speed      |
| <b>JM-1000 Mini-Jet</b><br>Page 26                   | Grease,<br>Sand,<br>Soft Stoppages,<br>and Ice                                 | 1/8" hose – 1-1/2" – 2"<br>(38 mm – 50 mm)                 | 50 ft. x 1/8"   | 23 lbs.<br>(10.4 kg)                      | 50 ft.<br>(15 m)   | 1.2 hp 13 amp                |
| <b>JM-1450 Electric Jet</b><br>Page 27               |  |  | 150 ft. x 1/4"  | 111 lbs.<br>(50 kg)                       | 150 ft.<br>(45 m)  | 1.5 hp 13 amp                |
| <b>JM-2900 Gas Jet</b><br>Page 28                    |  | 1/4" hose – 2" – 4"<br>(50 mm – 100 mm)                    | 200 ft. x 3/8"  | 180 lbs.<br>(82 kg)                       | 200 ft.<br>(60 m)  | 389 cc (13 hp)<br>Gas Engine |
| <b>JM-3000 Gas Jet</b><br>Page 29                    |  |  | 300 ft. x 3/8"  | 291 lbs.<br>(132 kg)                      | 300 ft.<br>(90 m)  | 389 cc (13 hp)<br>Gas Engine |
| <b>JM-3055 Gas Jet</b><br>Page 30                    |  | 3/8" hose – 4" – 8"<br>(100 mm – 300 mm)                   | 300 ft. x 3/8"  | 299 lbs.<br>(135 kg)                      | 300 ft.<br>(90 m)  | 480 cc (16 hp)<br>Gas Engine |
| <b>JM-3080 Gas Jet</b><br>Page 31                    |  |  | 300 ft. x 3/8"  | 375 lbs.<br>(170 kg)                      | 300 ft.<br>(90 m)  | 614 cc (20 hp)<br>Gas Engine |
| <b>JM-2512 Typhoon<br/>Trailer Jet</b><br>Page 32-33 |  | 1/2" hose – 4" – 12"<br>(100 mm – 300 mm)                  | 400 ft. x 1/2"  | 1900 lbs<br>(862 kg)                      | 400 ft.<br>(120 m)   | 690 cc (24 hp)<br>Gas Engine |

Use 1/4" Cables in 1-1/4" – 2" Lines, 5/16" Cables in 1-1/2" – 2" Lines, 3/8" Cables in 2" – 3" Lines, 1/2" and 9/16" Cables in 3"- 4" Lines (Not Roots), 5/8" Cables in 3"- 6" Lines, 3/4" Cables in 4"- 10" Lines, 5/8" Sectionals in 1-1/4" – 3" Lines, 7/8" Sectional in 2" – 4" Lines, 1-1/4" Sectional in 3" – 10" Lines.