

# Comparison Chart

## Power Drain Cleaners

	Typical Applications	For Use In Following Pipe Sizes	Maximum Capacity	Operating Weight	Maximum Recommended Distance	Motor Horsepower
<b>Super-Vee</b> Page 6	Sinks, Bathtubs, Roof Stacks	1-1/4" – 3" (30 mm x 75 mm)	35 ft. x 3/8", or 50 ft. x 1/4" or 5/16" (10.5 m x 9.5 mm) (15 m x 7.9 mm)	16 lbs. with 5 ft. x 3/8" (7 kg)	50 ft. (15 m)	3.2 amp Variable Speed
<b>Power-Vee</b> Page 7				34 lbs. (15kg)		
<b>Drain Rooter PH</b> Page 8				30 lbs. (13 kg)		1/5 hp
<b>Model DRZ-PH</b> Page 9						
<b>Mini-Rooter Pro</b> Page 12	Small Drains, Inside Work, On Roofs	2" – 3" and most 4" (50 mm – 100 mm) (Not For Roots)	75 ft. x 3/8" or 50 ft. x 1/2" (22.5 m x 9.5 mm or 15 m x 12.7 mm)	62 lbs. With 75 ft. x 3/8" (28 kg)	75 ft. (22.5 m)	1/3 hp
<b>Mini-Rooter XP</b> Page 13				92 lbs. With 75 ft. x 3/8" (42 kg)		
<b>Sewerooter T-4</b> Page 14	Small Drains with 9/16" Cable; Roots with 5/8" Cable	3" – 6" (75 mm – 150 mm)	100 ft. x 9/16" 75 ft. x 5/8" (30 m x 14.2 mm) (22.5 m x 15.8 mm)	158 lbs. (72 kg)	150 ft. (45 m)	1/3 hp
<b>Speedrooter 92</b> Page 15	Main Lines, Roots, Difficult Obstructions	3" – 10" (75 mm – 250 mm)	100 ft. x 5/8" or 3/4" (30 m x 15.8 mm or 19 mm)	220 lbs. (100 kg)	200 ft. (60 m)	1/2 hp (Optional 3/4 hp)
<b>Speedrooter XL</b> Page 16	Main Lines, Roots with 5/8" or 3/4" Cable; Small Drains with 9/16" Cable	3" – 10" (75 mm – 250 mm)	100 ft. x 9/16, 5/8" or 3/4" (30 m x 14.2 mm, 15.8 mm or 19 mm)	220 lbs. (100 kg)	200 ft. (60 m)	3/4 hp
<b>Maxi-Rooter</b> Page 17	Main Lines, Roots, Difficult Obstructions	3" – 10" (75 mm – 250 mm)	125 ft. x 3/4" 150 ft. x 5/8" (37.5 m x 19 mm) (45 m x 15.8 mm)	250 lbs. (114 kg)	200 ft. (60 m)	3/4 hp
<b>Root 66</b> Page 18	Small Drains, Inside Work, On Roofs	1-1/4" – 4" (30 mm – 100 mm)	Not Applicable	42 lbs. Without Sections (19 kg)	125 ft. x 5/8" Sectional 150 ft. x 7/8" Sectional (38 m x 15.8 mm) (45 m x 22.4 mm)	1/2 hp
<b>Rodrunner</b> Page 19	Main Lines, Roots, Difficult Obstructions	3" – 10" (75 mm – 250 mm)	Not Applicable	90 lbs. Without Sections (41 kg)	300 ft. (90 m)	3/4 hp
<b>Rodrunner Model E</b> Page 19	Main Lines, Roots, Difficult Obstructions	3" – 10" (75 mm – 250 mm)	Not Applicable	185 Without Sections (84 kg)	500 ft. (150 m)	6.5 hp gas Engine
<b>Flexi-Rooter 100</b> Page 24-25	Grease, Debris, Roots, Descaling, Wall to Wall Drain Cleaning	2" – 4" (50 mm – 100 mm)	50 ft. (15 m)	68 lbs. With 50 ft. Shaft (31 kg)	75 ft. (22.5 m)	4 amp Variable Speed
<b>JM-1000 Mini-Jet</b> Page 26	Grease, Sand, Soft Stoppages, and Ice	1/8" hose – 1-1/2" – 2" (38 mm – 50 mm)	50 ft. x 1/8"	23 lbs. (10.4 kg)	50 ft. (15 m)	1.2 hp 13 amp
<b>JM-1450 Electric Jet</b> Page 27			150 ft. x 1/4"	111 lbs. (50 kg)	150 ft. (45 m)	1.5 hp 13 amp
<b>JM-2900 Gas Jet</b> Page 28		1/4" hose – 2" – 4" (50 mm – 100 mm)	200 ft. x 3/8"	180 lbs. (82 kg)	200 ft. (60 m)	389 cc (13 hp) Gas Engine
<b>JM-3000 Gas Jet</b> Page 29			300 ft. x 3/8"	291 lbs. (132 kg)	300 ft. (90 m)	389 cc (13 hp) Gas Engine
<b>JM-3055 Gas Jet</b> Page 30		3/8" hose – 4" – 8" (100 mm – 300 mm)	300 ft. x 3/8"	299 lbs. (135 kg)	300 ft. (90 m)	480 cc (16 hp) Gas Engine
<b>JM-3080 Gas Jet</b> Page 31			300 ft. x 3/8"	375 lbs. (170 kg)	300 ft. (90 m)	614 cc (20 hp) Gas Engine
<b>JM-2512 Typhoon Trailer Jet</b> Page 32-33		1/2" hose – 4" – 12" (100 mm – 300 mm)	400 ft. x 1/2"	1900 lbs (862 kg)	400 ft. (120 m)	690 cc (24 hp) Gas Engine

Use 1/4" Cables in 1-1/4" – 2" Lines, 5/16" Cables in 1-1/2" – 2" Lines, 3/8" Cables in 2" – 3" Lines, 1/2" and 9/16" Cables in 3"- 4" Lines (Not Roots), 5/8" Cables in 3"- 6" Lines, 3/4" Cables in 4"- 10" Lines, 5/8" Sectionals in 1-1/4" – 3" Lines, 7/8" Sectional in 2" – 4" Lines, 1-1/4" Sectional in 3" – 10" Lines.